

SAMPLE SPECIFICATION ON DRAWINGS

©2007 Focus Collaborative, Inc – Specification and Quality Assurance Consultants
156 Prospect Avenue
Lansdale, PA 19446
Phone: 215.412.0601 Fax: 215.412.0602
2231 Route 50 P.O. Box 248
Tuckahoe, NJ 08250
Phone: 609.628.2390 Fax: 609.628.2393

SUBMITTALS

Upon Request from the Architect, submit product data and samples on manufacturer's as listed in these specifications, or as approved by Architect.

Manufacturer's Listing

Submit a complete list, by specification article name, of all manufacturers and product types provided. If the Contractor makes a substitution, the submitted manufacturer's product data and samples must be approved by the Architect.

Gypsum Board Assemblies

Manufacturers: United States Gypsum Company, Gold Bond Building Products.
Standard Gypsum Board: ASTM C36. Thickness indicated, ends square cut, tapered edges.
Accessories: Edge Trim: U shaped exposed reveal bead, as recommended by gypsum board manufacturer.
Joint Materials: ASTM C475; reinforcing tape, joint compound and water; glass coated fiber tape for backing board.
Fasteners: ASTM C1002 Type S12 hardened screws for gypsum board and corner beads.
Adhesive: As recommended by gypsum board manufacturer.
Install gypsum board over wood studs and joists, walls and ceilings in accordance with manufacturer's instructions and as detailed.

CERAMIC TILE

Ceramic Tile Manufacturers: American Olean, Dal Tile, or Crossville Ceramics.
Ceramic Tile Materials: Wall Tile: ANSI A137.1; size as indicated. Colors and patterns as selected by Owner.
Mortar and Grout Manufacturers: Mapei Corporation. W. R. Bonsal Co., or Laticrete International Inc.
Mortar and Grout Materials: Mortar Materials: TCA A118.4; Portland cement, sand, latex additive, and water.
Grout: Cementitious type with latex additive.
Install tile, mortar and grout in accordance with TCA Handbook for Ceramic Tile Installation; and tile manufacturer's instructions.

RESILIENT TILE FLOORING AND BASE

Manufacturers: Armstrong Contract Interiors, Azrock Industries, Inc., Kentile Floors, Inc.
Submit color and finish samples for VCT and vinyl base.
Vinyl Composition Tile: ASTM F1066; color and patterns as selected. Thickness: 1/8 inch. Tile Size: 12 x 12 inches.
Vinyl Base: FS SS-W-40, Type 2 vinyl; top set coved, 4 inch high, 1/8 inch thick, colors as selected. Premolded end stops and external corners, of same material, size, and color as base.
Accessories: Subfloor Filler: White premix latex. Primers and Adhesives: Type recommended by manufacturer.
Edge Strips: Flooring material.
Install resilient flooring in accordance with the manufacturer's instructions.

END OF SPECIFICATION